

**BACHARACH**  
The Measurable Difference

# LEAKATOR® 10

Combustible Gas Leak Detector

EASY-TO-USE



RELIABLE



Actual Size is 8.5 inches  
with 20" flexible probe

## BACHARACH MAKES LEAK DETECTION EASY

Bacharach's Leakator 10 is a low maintenance combustible gas leak detection unit, small enough to be operated with just one hand, yet loaded with the kind of advanced features and technology professionals demand.

Powered for up to 30 hours of continuous operation by alkaline C-cell batteries, Leakator 10 comes complete with a flexible 20-inch long probe for hard-to-reach areas and a patented solid state sensor that will last for up to five years. Leakator 10 allows you to pinpoint large and small leaks quickly, while checking a relatively large area in a short amount of time.

## Features & Benefits

- Visual Indicator  
10 Ultra-bright LEDs
- Audible Indicator  
Loud Audible Ticking Rate
- 30 Hour Battery Life  
Easily Replaced C-cells
- Sensitivity Thumb-Wheel  
Aids Pinpointing Leak Detection
- Operational Status LEDs  
English and International Systems
- Patented Solid State Sensor  
Plug-in Sensor, Five-year Typical Life
- 20 inch Flexible Probe  
Hard to Reach Locations
- Tough ABS Plastic Housing  
Durable and Rugged Use
- Carrying Strap  
Easy to Use
- UL Classified  
Intrinsically Safe
- CE Mark  
Electronic Performance Standard



## Specifications

Housing	Molded, three piece ABS plastic in bright yellow color. Includes carrying strap.
Power	Five alkaline C-cells, not provided. 30 hours typical life for continuous operation.
Warm-up Time	Automatic, self-check, about ten seconds to operational condition.
Sensor	Patented semiconductor type. Five year typical life. Plug-in replacement.
Probe	Self storing 20 inch flexible probe. Accommodates integral sensor.
Sensitivity	20 ppm useable sensitivity (methane).
Status Indicators	Visual: 10 ultra-bright red LED's. Audible: Variable speed ticking sound. Earphone available for use in noisy environments. Power-On ultra-bright green LED, Fail ultra-bright yellow LED, Low Battery ultra-bright yellow LED.
Environmental	23° to 130°F (-5° to 54° C), 10% to 90% relative humidity, non-condensing.
Physical	Leakator: 18oz. (0.51Kg), 8.5" x 2 1/4" x 1 3/4" (21.6 cm x 5.7cm x 4.4 cm). Case: Black HDPE, 17 oz. (0.48Kg) 10 1/2" x 7" x 3" (26.7cm x 17.8 cm x 7.6 cm).
Safety Approvals	UL Classified, intrinsically safe, for use in Class I, Division 1, Groups A, B, C, and D classified areas. CE Mark.
Warranty	One year limited warranty. See warranty card for more information.

## Ordering Information

PART NO.	DESCRIPTION
19-7051	LEAKATOR 10, in custom carrying case, UL Classified, CE Mark, flexible 20 inch probe for combustible gases and vapors, with instruction manual. (Batteries not included).
19-0398	Replacement sensor and matching resistor.
19-0397	Replacement rigid carrying case.
19-0403	Replacement flexible probe assembly.
51-2529	Earphone