

Capacitance + MultiMeter

Wide Capacitance Range to 20 milliFarad Plus Full Function DMM

Features:

- Large 0.8" LCD display
- Wide capacitance range to 20mF with 0.1pF max resolution
- Capacitance test Frequencies of 1MHz, 100Hz and 10Hz
- 0.5% Basic Capacitance accuracy
- Functions include Resistance, AC/DC Volage and Current
- Zero adjust knob for capacitance
- Wider ranges and more resolution
- Low battery, polarity and overrange indicators
- Triggering lamp indicates live circuits in dark environment
- Continuity beeper and Diode test
- Complete with test leads, 9V battery and protective rubber holster

Applications:

- Check the value of motor run and start capacitors
- Check for shorted or open capacitors
- Perform all multimeter functions for general purpose electrical tests and maintenance requirements



CAT II-600V

| Specifications | Range | Accuracy (%rdg+digits) |
|------------------|--|------------------------|
| DC Voltage: | 200mV,2V,20V,200V,1000V | ±(0.25%+2d) |
| AC Voltage: | 200mV,2V,20V,200V,750V | ±(1.2%+3d) |
| DC Current: | 20µA,200µA,2mA,20mA,200mA,2A | ±(0.8%+4d) |
| AC Current: | 20µA,200µA,2mA,20mA,200mA,2A, | ±(1.2%+3d) |
| Resistance (Ω): | 200,2K,20K,200K,2M,20M,200M,2000M | ±(0.8%+4d) |
| Capacitance: | 200pF,2nF,20nF,200nF,2µF,20µF,200µF,2mF,20mF | ±(0.5%+1d) |
| Continuity: | Threshold 30Ω, Continuity Beeper 2.5kHz | |
| Diode Test: | Maximum test current of 1.5 mA | |
| Triggering Lamp: | 100V to 1000VDC (750VAC) | |
| Dimensions: | 3.5x7.5x1.4" (88x190x35mm) | |
| Weight: | 10.6 oz (300 g) | |



Ordering Information:

380800Capacitance + MultiMeter
380800-NIST ..Capacitance + MultiMeter w/NISTCertificate
409996Vinyl Pouch Carrying Case