

13540 N. FLORIDA AVE.
SUITE 105
TAMPA, FLORIDA 33613
(813) 960-3445



Data-Chart[®] 5000
ORDERING INFORMATION
July 12, 2000



Data-Chart 6 and 12 Channel Color Display Paperless Recorder with RS232C Communication.

Recorder: Operates from 90 to 260Vac or 125Vdc, standard. 24Vdc operation available.
Measures 6 or 12 channels of DC voltage⁽¹⁾, DC current⁽¹⁾, Thermocouple⁽¹⁾ and RTD⁽²⁾;
Includes RS232C serial communication and internal RAM data buffer. RS485 available.

To specify your Data-Chart, complete the model number in the blocks below and enter pricing for each block.

MODEL NUMBER: **DC-5** — — — — — — —

Calculate Price ↓

Base Instrument

Input Channels

- 6 Channel Universal DC V/I, T/C and RTD N/C
- 12 Channel Universal DC V/I, T/C and RTD \$525.00

Display

- 5.6" Color Active Matrix \$500.00
- 5.0" Monochrome N/C

Power

- 90-260Vac / 125Vdc \$ N/C
 - 90-260Vac / 125Vdc \$ 25.00
 - 18-30Vdc* \$ 125.00
- * (Screw Terminal Power Connections)

Data Storage - Removable

- 3½" Disk Drive \$ N/C
- PCMCIA Memory Card Drive \$ 100.00

Input/Output Options

- No Alarm Outputs \$ N/C
- 6 Form C Contacts / 3 Digital Inputs \$ 295.00
- 3 Form C Contacts / No Digital Inputs \$ 195.00

Serial Communications

- RS232C - ESD Protection \$ N/C
- RS485 - Isolated \$ 200.00

Data Storage - Internal

- 1 Meg Internal RAM \$ N/C
- 2 Meg Internal RAM \$ 150.00

↔ **Total Data-Chart price - (See other side for Windows™ Companion software (SW-3T), memory cards, and other options)**
Add all prices listed.

Example Model Number: DC-5600-C-1-1-1-1-1 defines a 6 channel input, ac power, with disk data storage, 6 relay contact output RS232C communications and 1 Megabyte of internal RAM.